

CONVENTIONAL/TEACHER DESK SPECIFICATION

End panel supports, pedestal supports and/or C-leg supports

Standard features on student and teacher desk worksurfaces with end panel and/or pedestal support on one end:

- All particleboard worksurfaces without the worksurface steel understructure have 1" thick 45lb. density particleboard substrate and feature color-matched high-pressure laminate (HPL) on top and .5mm cabinet liner backer on bottom of worksurface.
- All particleboard surfaces and edges are finished and sealed with glue bonds to create moisture barrier
- Permanently attached 3mm color-matched or coordinating PVC edge band with ergonomic 1/8" radiused top edge bonded with hot-melt adhesive and trimmed flush on top and bottom to create pry-proof edge
- Worksurfaces with square corners have 3mm radius on vertical edge. Rounded corners (called Plane worksurface) have 2" radius on corners. 24" deep top has 11-7/8" radius. 30" deep top has 14-7/8" radius
- All worksurfaces feature pilot holes in all screw locations for easy installation
- 3" diameter plastic grommets
- See matrix for available offering.

Standard features on wood modesty panels and end panel supports:

- 3/4" thick 45lb. particleboard substrate with color-matched thermally fused laminate (TFL) on both sides for all horizontal and vertical outer and internal panels and shelves.
- No unfinished particleboard panels
- 3mm color-matched PVC edge band bonded with hot-melt adhesive
- Half-height and full-height modesty panels available on select desks

Standard features on wood pedestal storage and end panel support:

- Desks can be configured with 1) freestanding single pedestal with end panel on opposing side, 2) double pedestal, 3) freestanding single pedestal with metal support on opposing side, and 4) L-configuration with single pedestal desk and pedestal return in right or left-handed orientation
- 3/4" thick 45lb. particleboard substrate with color-matched thermally fused laminate (TFL) on both sides for all horizontal and vertical outer and internal panels and shelves.
- No unfinished exposed particleboard panels
- 3mm color-matched PVC edge band bonded with hot-melt adhesive
- 20-gauge cold-rolled steel drawer construction on box and file drawers mounted to 16", non-binding full-extension drawer slides on both box and file drawers. Drawers finished with electrostatically applied powder coating.
- Door and drawer pulls are ADA compliant arch-shaped pulls that are on 96mm on center, 132mm in length with 29mm projection
- Wood storage, modesty panels and end panels seated on 1-1/4" square 16-gauge steel tubular frame. Frame accepts casters and 2.75" high legs
- Caster or leg base options
 - Units with casters feature 75mm factory-installed nylon twin-wheeled swivel casters
 - Units with legs feature 2.75" tall 1-1/4" diameter 16-gauge steel tube with levelers welded to metal frame.
- Wood back panel seated on welded frame and attach to other sections of desk with #10x3" screws that pass through plastic support channels
- D-shaped worksurfaces feature metal C-leg support (on one end only). C-leg base is 1-1/4" square 16-gauge steel tube with polypropylene tube caps. Two vertical 1-1/4" square 16-gauge steel tubes are fully welded to base

and top tube. Top tube is 1-1/4" square 16-gauge steel tube that is connected to worksurface with #10x2" screws. Electrostatically applied powder coated paint.

- 3" diameter plastic grommet available. Open metal cable management trough standard.
- Factory-assembled units.

Worksurface and frame materials palette:

- Thermally Fused Laminate (TFL) available in woodgrains, solids, or patterns. 18 standard options with coordinating edgeband colors.
- High Pressure Laminate (HPL), for worksurfaces only, available in wood grain, patterned, or solid color palette. 18 standard options with coordinating or contrasting edgeband colors. Wilsonart laminates also available as a graded-in custom material.
- 4 standard paint options
- Custom TFL and HPL (worksurfaces only) through specials request process with coordinating 3mm vinyl edgeband.
- Buying relationships established with Wilsonart, Formica, Nevamar, Pionite/Panolam, and other suppliers.

Overall:

- Cloth blanket wrapped and carton packaging options are available. If cartoned, skids are made from recycled materials.

Warranty highlights:

- Fleetwood brand products carry a limited lifetime warranty, where products are warranted to be free of defects in materials and workmanship for the life of the product.
- Normal wear-and-tear is not covered under the warranty. Unauthorized alterations, improper maintenance, or abuse nulls warranty.
- Fleetwood will repair or replace free-of-charge any component that fails under normal use or provide refund or credit.
- Laminates, casters, levelers, and flip-and-nest mechanisms have a 12-year warranty.
- Some products have limited life coverage of 3 or 5 years. See full warranty statement for details.
- Consumables, natural variations in product, and select non-standard products not covered under limited lifetime warranty.
- See full warranty statement for details.