

STUDENT DESKS AND TABLES SPECIFICATION

Crank adjustable height legs

Standard features on desk/table worksurfaces with crank leg supports:

- All particleboard worksurfaces have 1" thick 45lb. density particleboard substrate and feature balanced construction with high pressure laminate (HPL) on top and .5mm cabinet liner backer on bottom of worksurface
- All particleboard surfaces and edges are sealed with glue bonds to create moisture barrier
- Permanently attached 3mm color-matched or coordinating PVC edge band with ergonomic 1/8" radiused top edge bonded with hot-melt adhesive and trimmed flush on top and bottom to create pry-resistant edge
- Worksurfaces with square corners have 3mm radius on vertical edge.
- In addition to standard HPL, maple butcherblock tops available.
- All maple block worksurfaces are 1-3/4" thick and feature Michigan solid maple butcherblock construction with naturally occurring color variation. Individual solids are bonded together under controlled pressure with resin adhesives. Maple is unstained and finished with environmentally friendly DuraKryl 102 coating to protect and preserve surface from moisture.
- All worksurfaces feature pilot holes in all screw locations for easy installation
- See matrix for overview of crank leg options

Standard features user-height adjustable base with crank:

- Worksurface height is adjustable from 27" to 38-1/2" high in user-defined height-adjustment increments
- 1" thick laminate and 1-3/4" maple block worksurfaces standard
- Single-acting fluid displacement lift system is manually driven by hand crank with telescoping aluminum table legs and partial height modesty panel.
- Full metal, bolt-together frame
- Leg assembly attaches to worksurface with #10x1.5" Truss head screws
- 30" long base feet with 53-1/2" between the feet
- 2" diameter threaded leveler with 1" of adjustment
- Maximum additional weight on particleboard worksurface is 400 pounds. Maximum additional weight on maple block worksurface is 350 pounds.
- Adjustable base ships assembled
- Electrostatically applied power-coat paint

Surface materials palette:

- High Pressure Laminate (HPL) available in wood grain, patterned, or solid color palette. 41 standard options with coordinating or contrasting edgeband colors. Wilsonart laminates also available as a graded-in custom material.
- Maple block worksurfaces are 1-3/4" thick and feature Michigan solid maple butcherblock construction with naturally occurring color variation. Individual solids are bonded together under controlled pressure with resin adhesives. Maple is unstained and finished with environmentally friendly DuraKryl 102 coating to protect and preserve surface from moisture.
- Custom HPL (worksurfaces only) through specials request process with coordinating 3mm vinyl edgeband.
- Buying relationships established with Wilsonart, Formica, Nevamar, Pionite/Panolam, and other suppliers.

Overall:

- Cloth blanket wrapped and carton packaging options are available. If cartoned, skids are made from recycled materials.

Warranty highlights:

- Fleetwood brand products carry a limited lifetime warranty, where products are warranted to be free of defects in materials and workmanship for the life of the product.
- Normal wear-and-tear is not covered under the warranty. Unauthorized alterations, improper maintenance, or abuse nulls warranty.
- Fleetwood will repair or replace free-of-charge any component that fails under normal use or provide refund or credit.
- Laminates, casters, levelers, and flip-and-nest mechanisms have a 12-year warranty.
- Some products have limited life coverage of 3 or 5 years. See full warranty statement for details.
- Consumables, natural variations in product, and select non-standard products not covered under limited lifetime warranty.
- See full warranty statement for details.

