

# GROUP TABLE SOLUTIONS SPECIFICATION

## Pedestal Base and Post Leg tables

### Standard features on table worksurfaces:

- All particleboard worksurfaces without the metal frame understructure have 1" thick 45lb. density particleboard substrate and feature balanced construction with high pressure laminate (HPL) on top and .5mm cabinet liner backer on bottom of worksurface.
- All particleboard surfaces or edges are sealed with glue to create moisture barrier
- Permanently attached 3mm color-matched or coordinating PVC edge band with ergonomic 1/8" radiused top edge bonded with hot-melt adhesive and trimmed flush on top and bottom to create pry-proof edge
- Worksurfaces with square corners have 3mm radius on vertical edge. Rounded corners have 2" radius on corners. Radius on other shapes varies based on worksurface shape.
- All worksurfaces feature pilot holes in all screw locations for easy installation

### Standard features on round steel pedestal (column with disc base):

- 4" diameter, 16-gauge steel column in 29", 36" and 40" heights. 6-gauge steel bracket welded to each end of column and attached to top and bottom plates with 3/8-16-1/4" panhead machine screws.
- 1/4" thick 12" diameter steel top plate
- 3/8" thick 27" diameter base with eight glides
- Base is attached to worksurface on site with two 3/8-16x1.25" panhead machine screws
- Electrostatically applied power-coat paint
- Grommets available. Field installed.
- Power technology options
  - Available field installed.
  - Byrne Salt disc-shaped unit for one outlet with 72" long cord in storm finish
  - Byrne Moire trapezoid tower-shaped x" high unit with power on 4 sides in storm finish. Has 72" long cord with circuit breaker
  - Byrne Burele rectangular x" H with x" wide sides with 4 power outlets on one side in storm finish. Has 72" long cord with circuit breaker
  - Byrne Burele rectangular x" H with x" wide sides with 2 power outlets, 2 USB and 1 HDMI on one side in storm finish. Has 72" long cord with circuit breaker

### Standard features on fixed-height post bolt-on table leg solutions with independent legs:

- Fixed legs available in round leg version with 1-1/2" diameter 14-gauge steel tubing
- 10-gauge 6"x6" steel plate welded to individual post leg assemblies supports worksurface
- Leg assemblies attach to worksurfaces with ten 7/8" phillips panhead black wood screws that facilitate easy installation and prove both snag-proof and tamper-resistant to students
- Worksurfaces have pilot holes in all screw locations.
- Threaded-stem leveler made of glass-filled black nylon 1.5" diameter base and 3/8x16 stainless steel screw glide with hexagon adjuster for up to .875" of vertical adjustment
- Electrostatically applied power-coat paint



### Surface materials palette:

- High Pressure Laminate (HPL) available in wood grain, patterned, or solid color palette. 41 standard options with coordinating or contrasting edgeband. Wilsonart laminates also available as a graded-in custom material.
- 4 standard paint colors.
- Custom HPL through specials request process with coordinating 3mm vinyl edgeband.
- Buying relationships established with Wilsonart, Formica, Nevamar, Pionite/Panolam, and other suppliers.

### Surface material options:

- Chemical resistant HPL have 1" thick 45lb. density particleboard substrate and feature balanced construction with high pressure laminate (HPL) on top and 5mm cabinet liner backer on bottom of worksurface.

### Custom features:

- Worksurface options available:
  - Custom worksurface shapes
  - Markerboard high pressure laminate, available in white
- Pedestal options available:
  - Custom paints
  - Custom heights

### Overall:

- Tables ship unassembled from the factory. Carton packaging skids are made from recycled materials.

### Warranty highlights:

- Fleetwood brand products carry a limited lifetime warranty, where products are warranted to be free of defects in materials and workmanship for the life of the product.
- Normal wear-and-tear is not covered under the warranty. Unauthorized alterations, improper maintenance, or abuse nulls warranty.
- Fleetwood will repair or replace free-of-charge any component that fails under normal use or provide refund or credit.
- Laminates, casters, levelers, and flip-and-nest mechanisms have a 12-year warranty.
- Some products have limited life coverage of 3 or 5 years. See full warranty statement for details.
- Consumables, natural variations in product, and select non-standard products not covered under limited lifetime warranty.
- See full warranty statement for details.

